

Product Data Sheet

SBO (Soybean Oil)

Technical grade soybean oil is used in paints, varnishes, alkyd resins, carriers, pharmaceutical mfg., defoamers (as mineral oil replacement), and similar applications.

Appearance: Clear

Product Properties

	Specifications
Color (Gardner)	2.0 maximum
Free Fatty Acids (%)	.10 max as oleic acid
Saponification Vlaue	188 - 195
Moisture & Volatiles (%)	0.10 maximum
Iodine Value	126 - 195
Average LBS/GAL @ 60 ° F	7.70

SAFETY INFORMATION: Please refer to MSDS
AVAILABLE FORMS / PACKAGING: Tank Truck-Totes-Drums
SHIPPING POINTS: Atlanta, GA

The Nottingham Company
Div. of Performance Process Inc.

Sales and Technical Service: Atlanta, GA. (404) 351-3501

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.