

Product: **PERFORM-O-SIL 70** Hydrophobic Precipitated Silica

Description: **PERFORM-O-SIL 70**
A Silicone Treated Silica with standard levels of hydrophobicity.

Properties:	Physical Data	Unit	Typical Values
	Specific surface area (BET)	m ² /g	70-80
	Average particle size	µm	7-8
	Bulk Density	lbs/ft ³	8-10
	pH	-	9-10
	Form	-	Powder
	Hydrophobicity Level	-	STD

Applications:

Application	General Functional Properties
<ul style="list-style-type: none"> • Defoamers/Anti-foams • Rheology • Powders 	Rheology control, Pigment dispersion, Pigment stabilization, Free-flow & Anti-caking agent for powders.

F.D.A. Status: Approved for use under: 21 CFR 176.200, 176.210 & 173.340

Packaging: 25 lb. Bags and 450 lb. Super sacks

Contact:

Performance Process Inc. 1515 Reidel Drive Mundelein, IL. 60060 Phone: 847-949-4080 Fax: 847-949-9486	Nottingham Company <i>(Div. of Performance Process, Inc)</i> 1303 Boyd Ave. N.W. Atlanta, Ga. 30325 Phone: 404-351-3501 Fax: 404-351-7731
--	--

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. Nothing herein is to be taken as permission, inducement or recommendation to practice any patented invention without a license.